νυικλυ

Solutions for refrigeration and air conditioning technology

LOKRING[®] Single Ring Mechanical tube joining system for refrigerant lines



CONTENTS

04	VULKAN			
	04	VULKAN in brief		
	07	VULKAN references		
08	LOKRING [®] SINGLE RING			
	08	The best connection		
	10	Functional principal		
	11	The benefits		
	12	Trend of raw materials		
14	REFRIGERATOR APPLICATIONS			
	16	The cycle system of a refrigerator		
	18	Evaporator section		
	22	Condenser section		
	26	Dryer section		
	30	Compressor section		
34	AREAS OF NEW APPLICATIONS			
40	TOOLS & FUNCTION			
	42	LOKRING [®] SINGLE RING		
	44	LOKPREP®		
	46	Pinch-off and assembly tool		
	48	Hydraulic flaring tool		
	50	Hydraulic assembly tool		
	52	Hydraulic aggregate		
54	LOKRIN	LOKRING SERVICE SOLUTIONS		
60	VULKAN WORLDWIDE			

62 ONLINE-SERVICE




THE VULKAN GROUP

SINCE 1979 VULKAN HAS DEVELOPED, MANUFACTURED AND MARKETED MECHANICAL TUBE JOINING SYSTEMS FOR REFRIGERANT LINES.

With five production sites, over 50 sales companies and around 1,400 employees at 18 locations worldwide, the VULKAN Group is one of the technology and market leaders in the field of marine, industrial and energy technology as well as refrigeration and air conditioning technology.

Under the slogan "We ensure that systems work better." we provide our customers with customized solutions that help to improve their systems both technically and economically.



MARKETS AND PRODUCTS

Due to its diversified business portfolio, the VULKAN Group - in line with the markets it serves - is made up of three divisions: Marine, Industry and Energy and Refrigeration and Air Conditioning.

EXPERTS FOR REFRIGERATION AND AIR CONDITIONING TECHNOLOGY

Originally developed for the most extreme conditions of aerospace applications, VULKAN'S LOKRING tube joining technology has been continuously developed for domestic and commercial refrigeration as well as air conditioning applications.

APPROVED SOLUTION

2,500,000,000 Lokring® connections

have been successfully used in the industrial volume production of refrigerators, freezers and air conditioning systems.

GLOBAL

1,000,000 LOKRINGS PER DAY

are produced in the five international production facilities of VULKAN on modern multi-spindle automatic lathe machines and shipped to 83 destination countries.

COST ADVANTAGE

7,000 CUSTOMERS

optimise their international competitive edge by using LOKRING tube connections as cost and quality benefit compared to brazed ones.

KNOW-HOW

650 UNIQUE TYPES OF LOKRING

are used at present by customers in order to optimally join tubes made of different materials and combinations of diameters.

QUALITY

100% QUALITY INSPECTION

of LOKRING based on automated industrial image processing as part of the certified VULKAN quality management system.

THE VULKAN GROUP

CUSTOMIZED SOLUTIONS FOR BRAZE-FREE TUBE CONNECTIONS

Since 1979, we have continuously applied the expert knowledge gained as an original equipment manufacturer for the industry to our braze-free tube connections, providing customized solutions for tube connections used in the manufacture, installation and maintenance of refrigeration and air conditioning equipment. As the market leader in braze-free, permanent tube connections, we can supply a matched system of tube connections in original equipment quality and with all necessary certifications for almost any installation or service application. This also includes the corresponding assembly tools and accessories.

EVERYTHING FROM A SINGLE SOURCE

Our customers receive everything from a single source from special development for specific customer requirements and in-house production to sales and service through local subsidiaries or authorized distributors. VULKAN's Refrigeration and Air Conditioning division is divided into the following business segments:

OEM | PRODUCTION

The LOKRING Single Ring technology is a method for connecting metallic refrigerant lines without brazing so that they are permanent and hermetically sealed. For this purpose, VULKAN constructs customised LOKRING tube connectors for any application based on the tube materials, dimensions and tolerances and the associated assembly tools. Whether it is a matter of optimising costs, improving quality, or solving a problem – LOKRING Single Ring is the answer!

The patented LOKRING tube connection system provides an innovative system of braze-free tube connectors for every installation situation in refrigeration and air conditioning technology.

VULKAN provides an innovative system of braze-free tube connectors for every repair situation in refrigeration appliances.

⊖ REPAIR OF VEHICLE A/C SYSTEMS

Our technology includes an innovative system of braze-free tube connectors as well as hose connectors for every repair situation in vehicle air conditioning systems & E-Vehicle battery cooling circuits.

RESEARCH AND DEVELOPMENT

For the last decades, experienced engineers have built new solutions for customers' applications in the development centre in Germany.

PRODUCT AND MANAGEMENT CERTIFICATION

The products of VULKAN Refrigeration and Air Conditioning have of course TÜV and UL product approval. Furthermore, the quality management system is certified according to ISO 9001 and the environmental management system according to ISO 14001. In addition, AEO certifications, leak tests and expert reports are available.

CLIMATE PROTECTION

Since our tube connections are hermetically sealed, we can ensure that no climate damaging refrigerants leak into the environment. Furthermore, LOKRING makes the use of environmental friendly but flammable refrigerants (HC) safer and allows the use of CO_2 (R744). Thus, by using LOKRING tube connections you make a contribution to the active protection of the environment.

SERVICE

Whether you are seeking planning and consultancy for optimising the refrigeration cycle system by using brazefree tube connections, support with the introduction of the LOKRING technology in production or after-sales service – everything is available locally with competent VULKAN technicians.

THE BEST CONNECTION - WORLDWIDE

Operating with five international production facilities, with 18 VULKAN subsidiaries and an additional 13 agencies worldwide, we ensure that LOKRING expertise is available on site throughout the world. This means that our customers have rapid access to our specialists and that the necessary solutions are quickly available exactly where they are needed.



CUSTOMER REFERENCES

A small selection from more than 7,000 satisfied customers:



THE BEST CONNECTION

THE LOKRING® SINGLE RING TECHNOLOGY is a method for connecting metallic refrigerant lines without brazing so that they are permanent and hermetically sealed. For this purpose, VULKAN constructs customised LOKRING tube connections for any application based on the tube materials, dimensions and tolerances and the associated assembly tools. The primary area of application is the manufacture of the refrigerant circuit in the series production of refrigerators and freezers. There are other applications for the manufacture of evaporators for automotive air-conditioning systems, for heat exchangers in refrigeration and air-conditioning technology (e.g. manufacture of heat pumps) or with the serial installation of refrigeration and air-conditioning technology (e.g. air-conditioning for buses). Whether it is a matter of optimising costs, improving quality or solving a problem – LOKRING® SINGLE RING is the answer!

REFRIGERATORS AND FREEZERS. This is where the use of LOKRING has been proven a billion times over for the last 40 years. Nonetheless, it is in this segment that many LOKRING SINGLE RINGs are being constructed at present for new applications so that an increasing number of brazed connections are being replaced by LOKRING.

You can find more information on pages 14 – 33.

AUTOMOTIVE AIR-CONDITIONING. LOKRING has been a supplier of tube connections for the initial fitting of air-conditioning components to leading suppliers in the automotive industry for many years. The LOKRING SINGLE RING is being used for the series manufacture of evaporators and heat exchangers made of aluminium.

7. 🗧 🕤

الرع

You can find more information on pages 36 – 37.



HOW CAN WE CONNECT YOU?

Would you like to cut costs, improve the quality or solve a problem while manufacturing a refrigerant circuit? Would you like to dispense with brazing at a specific connection or dispense with it completely?



*

•*•

Please contact VULKAN and we will find a solution for your application. You will find contact information on pages 60 - 61.

HEAT EXCHANGERS / HEAT PUMPS. Situations may arise while installing heat exchangers into a refrigerant circuit, resulting from constructionrelated or material-related constraints that make brazing impossible or uneconomical. An example of the solution for such a Cu–Ti tube connection in a Heat pump using LOKRING SINGLE RING is illustrated on page 39.



You can find more information on page 39.

BUS AIR-CONDITIONING. Aluminium lines are increasingly being used in the installation of bus air-conditioning systems due to cost and weight considerations. This is facilitated by the use of LOKRING SINGLE RING as an efficient and reliable alternative to brazing.

You can find more information on page 38.



FUNCTIONAL PRINCIPAL

THANKS TO THE CONICAL INNER CONTOUR of the LOKRING, the diameter of the outer tube is reduced during assembly to such an extent that the inner tube and the outer tube create a hermetically sealed metal-to-metal connection. The lifetime gas-tightness of the fitted connection is ensured by the state of permanent elastic pretension, which is produced by the radial forces of the LOKRING acting in the opposite direction to the connection between the outer tube and the inner tube.



THE BENEFITS

LOKRING[®] IS BETTER



LOKRING is the preferred alternative to brazing as it is more cost-effective, delivers better quality with less failure and leak rates, as well as being faster. Furthermore, it provides an excellent opportunity to switch tubes and components of the cycle system to cost saving materials (e.g. aluminium).

LOKRING[®] IS COST-EFFECTIVE



LOKRING directly saves the costs for silver braze and highly trained operators. Meanwhile, LOKRING indirectly reduces potential brazing cost implications that might occur through leaks, corrosion, harmful fumes, damage, burns or tube preparations. LOKRING may even reduce the number of joints needed and the consumption of expensive Cu components.

LOKRING[®] IS BETTER QUALITY



A correctly made LOKRING joint ensures both a zero failure rate and zero leak rate in both plant and field. In addition, the LOKRING joint is very clean both inside and outside and there is no possibility of damage and burns occurring from brazing inside a cabinet. Finally, it ensures that there is no corrosion on grinded St tubes and no hazardous brazing fumes.

A LOKRING jo

LOKRING[®] IS FASTER



A LOKRING joint needs just 10 seconds irrespective of the material combination. And the more LOKRINGs that are applied, the more significant becomes the time advantage.

FORWARD - LOOKING SOLUTIONS




As it is the preferred material for brazing, Cu material is extensively used in refrigerant cycle systems. However, Cu is heavy and expensive. For example, in the highly innovative automotive industry, all refrigerant lines are Al material. By "joining" LOKRING you can finally consider the new possibilities!

MATERIAL COMBINATIONS




As LOKRING can join any tube materials with the same level of quality, you can switch the components and tubes of the cycle system to the most feasible and most cost-effective material – regardless of brazing standards.



TREND OF RAW MATERIALS

COPPER, ALUMINIUM AND STEEL RAW MATERIAL. The applied raw materials for components and tubes in a refrigerant cycle system are an essential input factor behind the cost of production. The following price chart shows the price fluctuation and price differences of raw materials in recent years.




COPPER, ALUMINIUM, STEEL: CHART OF RAW MATERIAL PRICE | EURO PER KG

COPPER VERSUS ALUMINIUM AND STEEL. As copper is used for many components and refrigerant lines in the refrigeration industry, it plays a significant role in the cost of production. Due to the increasing, global demand for copper, it can be assumed that the price increase of recent years will continue or even intensify in the future. On top, the price has been fluctuating greatly, which makes cost planning very difficult. The prices of aluminium and steel on the other hand have not been fluctuating so much, confirming a certain level of price stability and at a much lower cost.

For obvious reasons, the automotive industry - which is particularly known for high cost pressure – is using only aluminium, which when taking into consideration the light weight (1/3 of the weight of copper), is the most economical material for components and refrigerant lines. However, with aluminium comes the challenge of brazing. With LOKRING, this is not a problem as it can easily join tubes of any material. Therefore, LOKRING can help you to reduce your production costs!

SILVER BRAZING. The cost of silver brazing is dependent on the following factors: silver price, gram (g) of silver braze per joint and the percentage (%) of silver in the brazing alloy. The following chart shows the silver price with its fluctuations over the years.



SILVER: CHART OF RAW MATERIAL PRICE | EURO PER KG

LOKRING VERSUS SILVER BRAZING: Silver brazing has become increasingly expensive. Furthermore, the silver price has been fluctuating greatly which makes the cost planning for brazing very difficult. The exposure to the anticipated future price increases of silver represents a significant risk in terms of any cost planning. Meanwhile, the price for LOKRING SINGLE RING is not only cost-effective but should also prove to be constant in the long term!



REFRIGERATOR APPLICATIONS

1

-1

71.7


REFRIGERATOR APPLICATIONS | 15

AN

Hunne mela


REFRIGERATORS **AND FREEZERS**

THE CYCLE SYSTEM OF A REFRIGERATOR can be segmented into four sections: evaporator, condenser, dryer and compressor. The segmented cycle system below is a no frost model comprising two condensers and it is displaying the maximum quantity of 12 LOKRING SINGLE RING applications (10 tube joinings and 2 tube sealings). As the cycle system is the heart of every refrigerator, these 12 points are essential as regards operability, reliability and thus the overall success of a refrigerator. In the following chapters of this catalogue we will discuss and outline the advantages of choosing LOKRING SINGLE RING solutions rather than opting for brazing each section and individual application.




12.

Charging tube



EVAPORATOR SECTION

EVAPORATOR SECTION. Generally, the evaporator is made of aluminium and as it is not possible to braze Al to Cu in the plant, the evaporator supplier has to supply the evaporator with Al to Cu connectors at suction, as well as on the capillary side. The manufacturer is then brazing the Cu suction tube and Cu capillary tube to the Al to Cu connectors inside the cabinet in the plant. Therefore, the conventional way results in a total of 4 joints: 2 Al to Cu connectors made by the eva-porator supplier and 2 Cu to Cu joints brazed by the manufacturer. However, by choosing LOKRING you can reduce the total number of joints to 2 Al to Cu joints or even 2 Al to Al joints and also experience plenty of associated advantages!






Evaporator > Suction line



02. Capillary tube > Evaporator





EVAPORATOR SECTION

EVAPORATOR > SUCTION LINE.

Straightforward Al to Cu joint.

01.

LOKRING SINGLE RING. When using LOKRING, no Al to Cu connectors by the evaporator supplier are required. The manufacturer can directly join the Al evaporator to the Cu suction line and to the Cu capillary tube with just 2 joints. There is no chance of damage, burning or health hazards due to brazing inside the cabinet and no skilled operator is required.

BRAZE-FREE TUBE SOLUTIONS

- No heat generation.
- No fire protection requirements or safety requirements.
- Rotary swaging of Al tube on capillary side of the evaporator is required.

HATERIAL COMBINATION

Easy connection of Al evaporator to the Cu suction line and to the Cu capillary tube.

🔇 COSTS

- \bigcirc No need for skilled operator.
- As the manufacturer is reducing the costs of 2 joints (no Al to Cu connectors by the evaporator supplier) the supplier of the evaporator can reduce the price for the evaporator.


QUALITY

- → 50% less potential of leaks, as the number of joints is reduced from 4 to 2.
- No chance of damage and burns from brazing inside the cabinet.
- \bigcirc Very clean both outside and inside.
- No risk of choking of capillary tube due to brazing.



CONDENSER SECTION

CONDENSER SECTION. This model of refrigerator has two condensers – a back-plate condenser and an additional side plate condenser. Therefore, in total, the condenser section has 3 critical joints. One St to St joint from the back-plate condenser to the liquid line and a second St to St joint from the side plate condenser to the back-plate condenser. The third joint from the hot gas line to the side plate condenser is a Cu to St or St to St joint. All 3 joints are brazed with expensive silver braze, which necessitates the preparation of the St tube and protection of the connection point against corrosion, and they all have a maximum leak rate.






Back-plate condenser > Liquid line

Side plate condenser > Back-plate condenser




05. Hot gas line > Side plate condenser





CONDENSER SECTION





PROBLEMS OF BRAZING

- For brazing these joints, silver braze of 30% is typically used.
- Due to critical joint, generally speaking, the most skilled operator is used to braze these joints.
- Maximum rate of leakages both in the plant and in the field.
- The potential to overlook faults at the braze seam of the St tubes is quite high.
- If tubes with a different kind of St material are preheated for brazing, the "weaker" tube gets brittle, resulting in damage.
- To avoid corrosion after removing the zinc coating, the connection points have to be painted or protected by a shrinking hose.
- The joint looks very unclean after brazing and scale removal is required.
- Protective equipment against harmful brazing fumes is necessary.

BRAZE-FREE TUBE SOLUTIONS

- As LOKRING is a cold connection you do not face any problems induced by brazing a St to St or Cu to St joint.
- The switch from brazing to LOKRING is easy and can be implemented immediately as no major changes are required.

↔ MATERIAL COMBINATION

Joining both St to St and St to Cu with LOKRING is a reliable, fast and easy operation that takes just 10 seconds.

COSTS

- $\textcircled{\begin{tmatrix} \hline \hline \end{tmatrix}}$ No need for expensive silver braze.
- \bigcirc No skilled operators required.
- O No extra costs through leaks in plant or after sales service costs.
- O No protective equipment required against harmful brazing fumes.

QUALITY

- $\textcircled{\begin{tabular}{ll} \hline \hline \end{array}}$ No leakages either in field or in production.
- \bigcirc No hazardous brazing fumes.

🕔 time


- No additional operation of applying paint or using shrinking hose for protection against corrosion.
- No scale removal of the soiled joint after brazing is required.

FORWARD-LOOKING SOLUTION

- Using LOKRING on the condenser(s) can reduce material costs as the wall thickness of tubes can be reduced to 0.3 mm.
- As the weight of Al is 1/3rd of St and the price is nearly double, costs can be reduced by using LOKRING and switching the condenser(s) from St to Al.

DRYER SECTION


DRYER SECTION. The dryer has 2 critical joints. One is the dryer to the capillary tube joint (Cu to Cu) which, when brazing, is most critical for choking or leakages, and this is worsened by the high rate of leakages from the field which result in extra costs in terms of after sales servicing. The second joint is the liquid line to the dryer joint (St to Cu), which is brazed with silver braze. A third application on the dryer is the LOKRING stopper for sealing off the charging tube.





Dryer service tube sealing










Liquid line > Dryer

08.



07.

DRYER SECTION

DRYER > CAPILLARY TUBE. Cu to Cu joint with maximum quality problems from leaks or chokes.

PROBLEMS OF BRAZING

- For proper brazing the joint needs to be preheated. As the capillary is very soft and its wall thickness is just 0.5 mm, the ID of the capillary may collapse and choke while preheating.
- Preheating and brazing this joint requires the most skilled of operators.
- Without an even preheating the capillary suffers micro porosity in the brazing flux, which results in

BRAZE-FREE TUBE SOLUTIONS

- As LOKRING is a cold connection, you will not experience any chokes or leaks induced by preheating, uneven preheating or high temperature of brazing.
- Modification of the dryer with extension of neck length to 12 mm is required.

very minute leaks occurring in the field.

- When brazing with the high temperature required by silver braze, the capillary tube can collapse and choke.
- Protective equipment is required against harmful brazing fumes.
- After brazing the capillary becomes brittle and may crack while handling resulting in leakages.


QUALITY

- Neither leakages in the field nor in production.
- No choking of the capillary tube by high temperature of brazing with silver braze.
- Very clean both inside and outside.
- O No harmful brazing fumes.

🔇 COSTS


- No need for silver braze.
 No high extra costs through blockages, leaks in the plant or after sales service.
- No need for skilled operators.
- No protective equipment required against harmful brazing fumes.

06.	DRYER SERVICE TUBE SEALING. The conventional method for sealing the service tube is ultrasonic welding.	
<u></u>		
	Look for more information about LOKRING stopper in the compressor section on page 33.	



COMPRESSOR SECTION

COMPRESSOR SECTION. There are 3 joints and 1 sealing of the charging tube on the compressor. All 3 joints on our (frost free) model are Cu to Cu joints. Brazing Cu to Cu joints is less critical and less expensive than joints comprising different tube materials. However, what appears to be an advantage for brazing comes at the cost of a high consumption of expensive Cu tube on the suction line and hot gas line. And if this is not enough, the brazing fumes are unhealthy and brazing becomes a risk in cases where hydrocarbons are used. Furthermore, the compressor is the most visible part of the cycle system and therefore brazing looks unprofessional, dirty and is often perceived as a low quality solution.








COMPRESSOR SECTION

LOKRING SINGLE RING. Through using LOKRING, there is the possibility of achieving reasonable cost savings by switching the material of the suction tube from Cu to Al and of the hot gas line from Cu to St. And of course with LOKRING there are no unhealthy fumes and no fire risks. LOKRING joints are clean both inside and outside and in the visible compressor section and therefore the refrigerator will look entirely professional and of the very highest quality.





25

Ē

AREAS OF NEW APPLICATIONS


D

D

4

in mining

AUTOMOTIVE A/C



AUTOMOTIVE A/C




BUS A/C



HEAT PUMPS









TOOLS & FUNCTION

TOOLS & FUNCTION | 41

DESIGN AND CALCULATION

- REQUESTED INFORMATION. Due to the wide range of size and tolerance of tubes, it is unfortunately not possible to catalogue all of the available LOKRING sizes in this brochure. The individually required LOKRING SINGLE RING is designed according to the tube samples and details that are provided by the customer. To enable the design and calculation of the most suitable LOKRING the following information is required:
- tube materials, tube dimensions, dimensional tolerances and the wall thickness of tubes.
- Iocation of the joining, which may cause stress such as vibration or torsion to the connection point.
- any physical or thermal manipulation on the tubes following the assembly of the LOKRING like bending or brazing.
- the refrigerant that is used in the system.

DESIGN, CALCULATION AND ARTICLE CODE. Based on the information provided by the customer, VULKAN will be able to both calculate and design the most suitable LOKRING SINGLE RING. VULKAN will supply an application drawing to the customer that will confirm the tube dimensions and tolerances, as well as the suitable LOKRING SINGLE RING SINGLE RING, by article code. This will be tested on the tube samples that are provided in their final configuration (flared, rotary swaged, straight) by the customer according to VULKAN's application drawing or just straight, for aluminium tubes that the customer will flare with VULKAN's flaring tool.



PERMISSIBLE AREAS OF APPLICATION

- Operating pressure:*
- ➔ Test pressure:
- Temperature range:
- ➔ Tube wall thickness:
- Tube diameter:

PN (nominal pressure) = 25 bar (362.5 psi) up to 50 bar (725 psi) P_p (4 x PN) = 100 bar (1450 psi) up to 200 bar (2900 psi) -50°C up to +150°C (-58°F up to 302°F) 0.3 mm up to 1.5 mm 1.6 mm up to 28 mm

* Depending on tube materials.

LOKRING[®] SINGLE RING




LOKRING[®] SINGLE RING



LOKRING SINGLE RING is a custom designed product for each application. Its design takes into account the tube materials that are being joined, the wall thickness and the diameters of the tubes. It is both an approved and certified system for the joining of metallic tubes.

- Permanent hermetically metal-to-metal sealing.
- Enables tubes consisting of different tube materials to be easily connected.
- ➔ High reliability.
- No special preparation of the tubes required.
- ⊖ Easy and fast assembling in 10 seconds.
- → Handy assembly tools.
- Considerable tolerances in dimensions are permitted.
- \bigcirc Clean joint both inside and outside.
- No welding, brazing or screw cutting.
- O Ecologically and health wise harmless system.


FUNCTION



Metal tubes can have production-related longitudinal grooves or surface scratches. However, these faults can be compensated for by moistening the surfaces of the tube ends that are to be connected with LOKPREP fluid prior to assembly. Thanks to its capillary characteristic, it automatically covers the surfaces of the inserted tubes and flows into microscopic cavities and fills these out completely.

Rather than being an adhesive, LOKPREP is in fact an anaerobic sealant that hardens under oxygen exclusion and when in contact with free metal ions. At the end of the hardening process the LOKPREP sealant retains a permanently elastic structure. This means that it does not get brittle and therefore compensates for material-specific deformations.

There are different types of LOKPREP in order to achieve an optimal effect that is primarily dependent on the materials used, the installation conditions and the ambient temperature. The choice of the LOKPREPs to be used is defined by VULKAN after the customer specifies the application.



LOKPREP[®]



LOKPREP®




LOKPREP was developed especially for LOKRING assembly and must always be used wherever LOKRINGs are to be fitted. LOKPREP is used to provide additional safety in LOKRING connection technology and it compensates for possible unevenness in the tube surface, such as longitudinal grooves or surface porosity. Consequently, it guarantees that every LOKRING connection is hermetically sealed.

Article name	Quantity	
LOKPREP 61AL	50 ml	
LOKPREP 61S	50 ml	

LOKPREP is developed and manufactured exclusively for VULKAN. No other product has the specific material characteristics required in order to ensure fault-free and sealed LOKRING tube connections permanently and reliably.

OPERATIONAL INSTRUCTION






After finishing the charging, simply enter the tube into the recess of tool jaws and pinch off the tube by closing the hand slide valve situated at the end of the tool. You can release the tool by opening the hand slide valve.




Add LOKPREP (approximately 3 mm from the tube end). Put on the LOKRING stopper with a slight motion of rotation to ensure a better distribution of the LOKPREP.





Insert the stopper which is placed on the tube in the tool jaws to ensure that the tube is fully inserted into the stopper. By operating the hand slide valve, the LOKRING is pressed over the collet and seals the tube.



PINCH-OFF AND ASSEMBLY TOOL



PINCH-OFF AND ASSEMBLY TOOL



Pneumatic pinch-off and assembly tool for the leak-proof, clean and rapid sealing of the tube ends after charging the system with refrigerant agent, without welding or brazing.

Pneumatic pinch-off and assembly tool with two single acting pistons and exchangeable jaws. The actuation is set off through the sliding valve. Please note that only through using the LOKRING stopper can one guarantee the absolute closure of the sealed tube.


Tube requirements

The pneumatic pinch-off and assembly tool is only suitable for copper tube according to EN 12735-1 (R220) or EN 12735-2 (Y035) with a tensile strength of minimum 40% or equivalent tube.

Technical data


Soft copper
6 and 6.35 mm
0.7 mm
1.0 mm
8-9 bar (116-130 psi)
9 bar (130 psi)
G ¼
2.0 kg
approx. ø76 x 350 mm

OPERATIONAL INSTRUCTION






The clamping jaws have to be opened by hand and the tube end that needs to be flared must be inserted between the clamping jaws up to the flaring insert.





Through the actuation of the start button the tube is clamped by the clamping jaws and flared by the flaring insert. 

The flared tube can be removed from the tool after the flaring process has been completed.



HYDRAULIC FLARING TOOL



HYDRAULIC FLARING TOOL




The hydraulic flaring tool is designed for the flaring of aluminium tubes for the production of LOKRING SINGLE RING tube joinings. It is connected to the LOKRING hydraulic aggregate by two 2.8 m hydraulic hoses. The forward and backward movement of the flaring insert is enabled by means of a double acting cylinder. The size of the clamping jaw and the flaring insert depends on the outside tube diameter.

Technical data

Suitable tube material:	Aluminium
Max. tube outside diameter:	1/2" / 12.7 mm*
Max. tube wall thickness:	1.0 mm*
Operating pressure:	up to 300 bar
Flaring time:	approx. 1 sec.
Weight:	approx. 1.6 kg
Dimensions:	45 x 74 x 250 mm

OPERATIONAL INSTRUCTION







Slide the LOKRING over the inner tube so that the chamfer faces towards the tube end to be joined. Move the inner tube into the outer tube to at least "the length of the LOKRING + 3 mm" (in cases involving flared tubes, it should be up to the stop) and apply LOKPREP between the mated tubes. Place the tool in such a way that the clamping jaws are positioned on the side of the outer tube and the LOKRING can be pushed to the end of the outer tube.



Following the actuation of the start button, the outer tube is clamped by the clamping jaws and the LOKRING is pushed over the outer tube. After the assembly, the tool switches off automatically and can be removed from the tube joining.





HYDRAULIC ASSEMBLY TOOL



HYDRAULIC ASSEMBLY TOOL




The hydraulic assembly tool enables the LOKRING connection of tubes with similar or different tube diameters. The production of the joining requires no special preparation of the tubes and can be carried out by unskilled workers. The tool is connected to the LOKRING hydraulic aggregate by a 2.8 m hydraulic hose. The sizes of the clamping and assembly jaws are dependent on the dimensions of the tubes that are to be joined.

Technical data

Max. tube outside diameter	r: 7/8" / 28 mm*
Max. tube wall thickness:	1.5 mm*
Operating pressure:	up to 300 bar
Assembly time:	approx. 2 sec.
Weight:	approx. 3.0 kg
Dimensions:	approx. 315 x 80 x 50 mm

TYPES



Article		Article no.	Voltage	Tools			
	HA-230V-2HAT HA-400V-2HAT	L13006274 L13006276	230V, 1 Phase 400V, 3 Phase	2 Hydraulic assembly tools	u S S S S S S S S S S S S S S S S S S S		
	HA-230V-1HAT-1HFT HA-400V-1HAT-1HFT	L13006275 L13006277	230V, 1 Phase 400V, 3 Phase	1 Hydraulic assembly tool 1 Hydraulic flaring tool		₩ 0, ₩	

HYDRAULIC AGGREGATE



HYDRAULIC AGGREGATE



The LOKRING hydraulic aggregate produces the required working pressure for the flaring and assembly tools. The aggregate is transportable and, according to its application, it is available at each workplace. The LOKRING tools are connected to the hydraulic aggregate by quick connections and hydraulic hoses. To actuate the aggregate, simply push the remote control switch that can be found on the tool. The hydraulic pressure is controlled by a switch and control gear, as well as control valves to the tools.

Technical data

Power:	1.1 kW
Power supply:	230 V or 400 V (±10 %)
Number of revolutions:	2800 min ⁻¹
Frequency:	50 Hz
Current consumption 230 V:	9 A
Current consumption 400 V:	3,7 A
Protection class:	IP 54
Output:	2.5 l/min
Operating pressure:	up to 300 bar (adjustable)
Dimensions:	400 x 300 x 600 mm
Weight:	28 kg (including oil)



VULKAN DOV LOKRING® SERVICE SOLUTIONS

LO


LOKRING SERVICE SOLUTIONS | 55

LOKRING SERVICE SOLUTIONS



ENDLESS POSSIBILITIES

THE PATENTED LOKRING[®] TUBE CONNECTION SYSTEM provides an innovative system of braze-free tube connections for every repair situation in refrigeration appliances. LOKRING tube connections can be made without a great deal of force being necessary, using simple hand assembly tools. LOKRING ensures an absolutely clean, permanent and purely mechanical tube connection with long-term hermetic gas-tightness. This is confirmed by the special TÜV test and approval. All this makes LOKRING tube connections one of the most economical and reliable methods of connecting refrigerant tubes.



THE BENEFITS

- Also suitable for flammable refrigerants
- Oustomer-friendly onsite service
- Absolutely clean, efficient and reliable
- Repair work during business hours and public access
- Repair work in situations where there is a fire hazard
- Dight hand assembly tool without energy exertion
- No brazing related quality problems

ONE SYSTEM - ENDLESS POSSIBILITIES

- Straight connections
- Straight reducing connections
- Onnections with schrader valve
- O Capillary connections
- Elbows
- T-connections
- Stoppers


AREAS OF APPLICATION

- Household refrigeration appliances (refrigerators, freezers, wine coolers)
- Ready-to-use refrigeration equipment (refrigeration cabinets, bars, lockers, chillers)
- Refrigeration equipment for catering (sales counter refrigerators, flow-through coolers, portable cooling systems)

WITH LOKRING YOU CAN

- Replace a compressor
- Replace a dryer
- Replace a charging tube
- Repair leaky tubes

LOKRING SERVICE SOLUTIONS






COMPONENTS



MATERIAL COMBINATIONS








COMPONENTS



MATERIAL COMBINATIONS



ALUMINIUM COPPER

STEEL

BRASS / ALUMINIUM CONNECTORS

THE TYPICAL LOKRING union joint consists of two LOKRINGs and one tubular joint for the acceptance of the two tube ends. Thanks to the conical inner contour of the LOKRING and the special outer contour of the joint, the diameter of the connection is reduced during assembly to such an extent that the joint and the tube create a hermetically sealed metal-to-metal connection. The lifetime gas-tightness of the fitted connection is ensured by the state of permanent elastic pre-tension, which is produced by the radial forces of the LOKRINGs acting in the opposite direction to the tube-joint connection.





TECHNICAL SPECIFICATIONS BRASS CONNECTORS

Reference standards:	EN 378-2
Max. operating pressure:	25 bar* (3
Admissible refrigerants:	Suitable f Not suitat
Temperature range:	-50°C up t
Tube diameter range:	1.6 to 11 r
Minimum tube wall thickness	: 0.5 mm
Approvals:	TÜV, UL (

EN 378-2 and ISO 14903 25 bar* (360 psi*) Suitable for all HCs, HFCs and mixtures. Not suitable for NH₃. -50°C up to 150°C (-58°F up to 302°F) 1.6 to 11 mm (1/16" to 3/8") 0.5 mm TÜV, UL (File SA12004)

TECHNICAL SPECIFICATIONS ALUMINIUM CONNECTORS

Reference standards:	EN 378-2 and ISO 14903	
Max. operating pressure:	25 bar (360 psi)	
Admissible refrigerants:	Suitable for all HCs, HFCs and mixtures. Not suitable for $\ensuremath{NH}_3.$	
Temperature range:	-50°C up to 150°C (-58°F up to 302°F)	
Tube diameter range:	2 to 9 mm (5/64" to 5/16")	
Minimum tube wall thickness: 0.5 mm		
Approvals:	TÜV, UL (File SA12004)	

*Solutions for higher operating pressures on request.

THE BEST CONNECTION -WORLDWIDE

UNITED STATES OF AMERICA

American VULKAN Corporation 2525 Dundee Road 33884 Winter Haven, Florida Phone +1 863 3 24 24 24 E-mail us.info@vulkan.com

→ BRAZIL

VULKAN do Brasil Ltda. Rodovia Engenheiro Constâncio Cintra, km 91 13252-200 Bairro da Ponte, Itatiba -SP Phone +55 11 48 94 73 00 E-mail br.marketing@vulkan.com

NETHERLAND

VULKAN Benelux Van Coulsterweg 3 2952 CB Alblasserdam Phone +31 78 6 81 07 80 E-mail info@vulkan-benelux.com

GREAT BRITAIN

VULKAN Industries Ltd. Archer Road Armytage Road Industrial Estate HD6 1XF Brighouse, West Yorkshire Phone +44 14 84 71 22 73 E-mail uk.info@vulkan.com

FRANCE ----VULKAN France SA

12, Avenue Emile Zola, Zac de L'Agavon 13170 Les Pennes Mirabeau Phone +33 4 42 02 21 06 E-mail Loic.Daurelle@vulkan.com

🗩 SPAIN 🗉

VULKAN Española S.A. Avda. Montes de Oca 19, Nave 7 28709 San Sebastián de los Reyes, Madrid Phone +34 91 3 59 09 71 E-mail es.info@vulkan.com

ITALY

VULKAN Italia Srl Via dell'Agricoltura 2 15067 Novi Ligure (AL) Phone +39 01 43 31 02 11 E-mail it.info@vulkan.com

Ə SOUTH AFRICA 🛛

VULKAN South Africa (Pty) Ltd 4 Sedgewick Road, Founders View South, Lethabong, Edenvale, 1609, South Africa Phone +27 11 6 09 13 39 E-mail info@vulkansa.co.za

GERMANY

VULKAN Lokring Rohrverbindungen GmbH & Co. KG Heerstraße 66, 44653 Herne Phone +49 23 25 92 21 55 E-mail info.lok@vulkan.com

THE STAR

TURKEY

VULKAN Turkey Engineering, Marineand Industrial Products Trading Ltd. StiEsentepe Mah. Nato Yolu Cad. No: 25034776 Umraniye - IstanbulPhone+90 216 6 80 05 35 36E-mailkagan.hasircioglu@vulkan.com

KORE/

VULKAN Korea Corporation 57, Ballyongsandan 1-ro, 46034 Jangan-eup, Gijang-gun, Busan Phone +82 51 2 56 24 73 E-mail sungchan.bang@vulkan.com

JAPAN

Ð

Nippon VULKAN Co., LTD. 6-28 Nishikobari, Ina-machi Kitaadachi-gun 362-0811 Saitama Phone + 81 4 87 29 02 02 E-mail jp.info@vulkan.com

) CHINA

 WUXI VULKAN Technologies Co., Ltd.

 Xinzhou Road, Lot 93D-3

 in Wuxi Science & Technology Industrial Park

 214028 Jiangsu Prov. P.R.China

 Phone
 +86 05 10 85 34 22 22

 E-mail
 service@vulkanchina.com

🔿 AUSTRALI*I*

VULKAN Australia PTY LTD 35 Pile Road NSW 2250 Somersby Phone +61 (02) 43 40 22 78 E-mail stephen.samson@vulkan.com

SINGAPORE ··· VULKAN Industries

 Far East Pte Ltd

 37C Benoi Road, Pioneer Lot

 627796, Singapore

 Phone
 +65 65 78 96 90

 E-mail
 sg.info@vulkan.com

🕀 INDIA

Ŀ,

VULKAN Technologies Pvt. Ltd Gat No. 1097/1102, Urawade Road Pirangut Industrial Area 412 115 Tal. Mulshi, Dist. Pune Phone +91 20 66 76 54 00 E-mail in.info@vulkan.com

ONLINE-SERVICE

FOR FURTHER INFORMATION, PLEASE REFER TO OUR WEBSITE **WWW.VULKAN.COM**



IMPRINT

PUBLISHER:

VULKAN Lokring Rohrverbindungen GmbH & Co. KG Heerstraße 66, 44653 Herne / Germany Tel.: + 49 (23 25) 922-155 E-mail: info.lok@vulkan.com

CONCEPT AND DESIGN:

Hackforth Holding GmbH & Co. KG VULKAN Marketing Heerstraße 66, 44653 Herne / Germany E-mail: marketing@vulkan.com

PREPRESS:

Hackforth Holding GmbH & Co. KG VULKAN Marketing Heerstraße 66, 44653 Herne / Germany E-mail: marketing@vulkan.com

VALIDITY CLAUSE

The LOKRING[®] tube connection technology represents a proven method of producing hermetically sealed metal-to-metal tube connections. The LOKRING[®] tube connections are mainly used in the refrigeration and air conditioning industries. The use of LOKRING[®] tube connection technology in other fields is to be discussed with VULKAN. VULKAN as the supplier is responsible for the qualitative delivery of the tube connections and tools which are ordered from this catalogue.

The purchaser is responsible for the use of the LOKRING[®] tube connections and tools as directed. The assembly has to be done accordingly to the instructions and exclusively with original LOKRING[®] parts. The present LOKRING Single Ring catalogue shall replace all previous editions, any previous printings shall no longer be valid. The data contained in this catalogue refers to the valid state of affairs in time of the copy deadline. Any changes due to technical progress are reserved.

Status: 01/2024

All duplication, reprinting and translation rights are reserved. Further remarks for the LOKRING® assembly are available on request.

Article no.: L19000007



www.vulkan.com/en-us/lokring/videos/